



Product Data

Castrol MAGNATEC 0W-30 D

NON-STOP PROTECTION FROM EVERY START

Description

Castrol MAGNATEC has been developed to meet the unique demands of modern driving.

75% of engine wear can happen when we start the ignition. And acceleration, slowing down, and idling journeys in city driving only increase this strain. That means every congested commute, weekend getaway, and shopping trip may increase engine wear.

Castrol MAGNATEC clings like a magnet to critical engine parts and locks in place to deliver 50% better engine wear protection*. Helping to safeguard your engine's vital components - the valvetrain, timing chain, pistons, and bearings - from damage and wear.

Choose non-stop protection from every start. Choose Castrol MAGNATEC.

For more product information, visit castrol.com.

#ClingsLocksProtects

** Tested using an industry standard wear test, measured versus relevant industry limit.*

Application

Castrol MAGNATEC 0W-30 D is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an API SP, ACEA C2 or earlier specification 0W-30 lubricant.

Advantages

Castrol MAGNATEC clings, locks, and protects to deliver 50% better engine wear protection*.

Helping to safeguard your engine's vital components by:

- Forming a resistive barrier between metal contact points in the valvetrain
- Managing abrasive piston deposits, guarding against cylinder liner wear
- Maintaining timing chain tension and engine synchronicity by minimising chain damage and elongation
- Preserving engine bearings from corrosive wear

** Tested using an industry standard wear test, measured versus relevant industry limit.*

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC 0W-30 D
Density @ 15C, Relative	ASTM D4052	g/ml	0.846
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	53
Viscosity Index	ASTM D2270	None	179
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5600
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	200
Total Base Number, TBN	ASTM D4739; ASTM D2896	mg KOH/g	9.8
Ash, Sulphated	ASTM D874	% wt	0.80

Performance

ACEA C2

API SP

ILSAC GF-6

Meets Ford WSS-M2C957-A1

Meets Ford WSS-M2C950-A

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC 0W-30 D

22 Dec 2025

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com