



Garden 4T 10W-30

Enhanced durability

Description

Castrol Garden 4T 10W-30 is a modern engine oil for garden machinery. Its formulation ensures enhanced engine durability.

Application

For garden machinery with gasoline or diesel engines where manufacturer recommends API SL or API CF or earlier specifications.

Advantages

- Multigrade 10W-30
- Enhanced engine durability
- Wide range of application: suitable for 4T garden equipment with gasoline or diesel engines requiring API SL or API CF or earlier specifications

Typical Characteristics

Name	Method	Units	Castrol Garden 4T 10W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.8708
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	10.92
Viscosity, Kinematic 40C	ASTM D445	mm²/s	70.710
Viscosity Index	ASTM D2270	None	144
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	200.5

Product Performance Claims

API SL/CF

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com