



Transmax Universal LL 75W-90

Universal Fluid for manual transmissions and axles

Description

Castrol Transmax Universal LL 75W-90 formulated with Smooth Drive Technology™ is a full synthetic multi purpose manual transmission and final drive lubricant. It may be used in synchronised manual transmissions and final drives / differentials of a wide range of vehicles (commercial vehicle, construction equipment) where API GL-4 or API GL-5 fluids are required and it carries a number of OEM approvals.

Advantages

- A single product for transmissions and final drives reducing inventory and the potential for misapplication.
- Excellent low temperature fluidity provides improved shift quality and wear protection in cold conditions and improves fuel efficiency.
- Superior high temperature stability and excellent wear protection even in the most arduous conditions prolongs equipment life and allows for extended drain intervals.
- Full compatibility with conventional mineral oils and seals allows this product to be used in a wide range of applications.

Typical Characteristics

| Name | Method | Units | Transmax Universal LL 75W-90 |
|------------------------------------|--------------|--------------------|------------------------------|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.8665 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 15 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 104 |
| Viscosity Index | ASTM D2270 | None | 154 |
| Viscosity, Brookfield @ -40C (75W) | ASTM D2983 | mPa.s (cP) | 67000 |
| Pour Point | ASTM D97 | °C | -51 |
| Flash Point, COC | DIN-ISO 2592 | °C | 202 |

Product Performance Claims

API GL-4/GL-5/MT-1
SAE J2360
MAN 341 Z2, 342 S1, MB-Approval 235.8,
Scania STO 1:1G, STO 2:0A FS,
Volvo 97312,
ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A

Additional Information

Transmax Universal LL 75W-90 is registered under the following ZF approval numbers: ZF002144

Transmax Universal LL 75W-90
02 Jun 2022
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com