



APPLICATIONS

Eni Acer 22 is a lubricant for circulation systems and oleodynamic circuits where antirust and antioxidant properties are required.

Eni Acer 22 is particularly recommended for lubrication of journal and rolling bearings, crank mechanisms and gear couplings that are not demanding antiwear or E.P. performances, joints and wet clutches not for automotive applications.

CUSTOMER ADVANTAGES

- Quick separation from water that could accidentally enter the system thanks to optimal demulsive capacity
- Effective protection from rust and corrosion
- Oil film continuity and incompressibility ensured by a quick antifoam and air release action
- Compatibility with rubber types that are commonly used for seals

SPECIFICATIONS & APPROVALS

- CETOP RP 91 H HL
- BS 4231 HSC
- AFNOR NF E 48600 HL
- DIN 51524-1 HL
- ISO 11158 L-HL





CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	868
Viscosity at 40°C	ASTM D 445	mm ² /s	22
Viscosity Index	ASTM D 2270	-	109
Flash point (COC)	ASTM D 92	°C	210
Pour point	ASTM D 97	°C	-30
Demulsibility at 54°C	ASTM D 1401	mins	15
Rust test/B	ASTM D 665	-	pass

WARNINGS

- **Eni Acer 22** must not be used in systems operating with lubrication in boundary conditions or where antiwear or E.P. performances are required.



eni