

# Eni i-Ride scooter 2T



## APPLICATIONS

**Eni i-Ride scooter 2T** is a synthetic technology lubricant that provides very low smoke in 2-stroke engines that are fitted in scooters, either cooled with liquid or air.

## CUSTOMER ADVANTAGES

- **Eni i-Ride scooter 2T** scooter minimizes the formation of deposits in the combustion chamber, in the exhaust clearances, and in the piston rings grooves. Its characteristics ensure a good detergency of the engine components.
- **Eni i-Ride scooter 2T** scooter preserves the surfaces of the mechanical parts from the presence of wear.
- **Eni i-Ride scooter 2T** scooter is formulated specifically for use in vehicles equipped with separate mixing systems, but can also be used for manual mixing.

## SPECIFICATIONS - APPROVALS

- API TC
- JASO FC





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	871
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	10.3
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	73
Viscosity Index	ASTM D 2270	-	124
Flash point (COC)	ASTM D 92	°C	118
Pour point	ASTM D 97	°C	-15

